



STRIPPING DIMENSION

NOTES: UNLESS OTHERWISE SPECIFIED

1. BODIES: BRASS PER JIS-C3604
2. CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17300
3. INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
4. CONNECTOR INTERFACE PER MIL-STD-348A
5. PART TO BE CLEAN AND FREE OF BURRS

8	CENTER CONTACT	BERYLLIUM COPPER	1	SILVER 70 μ " MIN.
7	NUT	BRASS	1	SILVER 70 μ " MIN.
6	WASHER	BRASS	1	SILVER 70 μ " MIN.
5	GASKET	SILICONE	1	RED
4	SLEEVE	BRASS	1	SILVER 70 μ " MIN.
3	BODY	BRASS	1	SILVER 70 μ " MIN.
2	SLEEVE	BRASS	1	SILVER 70 μ " MIN.
1	INSULATION	TEFLON	1	NONE
NO	DESCRIPTION	MATERIAL	Q'TY	FINISH

APPROVED

by _____ DATE: _____

DESCRIPTION		N STRAIGHT JACK CLAMP		DATE		REV.	
製圖	DRAWN	TOLERANCE	品名	11-02-3	213U (50U)	日期	06.18.92'
	Elvis						
檢圖	CHECK	.XX	單位	DWG.NO.	11-0014	SCALE	比例
	Pony	±0.1					
認定	APPROVAL	.XXX	±0.05	佳楠精密電子股份有限公司 CHIN NAN PRECISION ELECTRONICS CO.,LTD.			
Pony	ANGLE	±5°					